




















Product Catalog



CEMENT BASED TILE ADHESIVE MORTAR

CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRACK	CONSUMPTION	PACK TYPE
CE-101	 <p>SERAWEB TILE ADHESIVE MORTAR</p> <p>Cement based tile adhesive mortar. It's used in indoor places horizontally and vertically, in outdoor places and for the adhesion of coating materials like tiles, tiles, faience, tiles, glass mosaic etc. ,in outdoor places on the horizontal surfaces. EN 12004 C1 T Class</p>	Gray	25 Kg. Craft Bag	64-80 Bag	5 KG/M2	
CE-102	 <p>SERAPLUS HIGH PERFORMANCE TILE ADHESIVE MORTAR</p> <p>High performance, single component, cement based, flex adhesive mortar with reduced waiting time on the extended shift feature It is used for bonding coating materials like floor and wall Tile tiles, glass mosaic indoors and outdoors. EN 12004 C1 TE Class</p>	Gray	25 Kg. Craft Bag	64-80 Bag	5 KG/M2	
CE-103	 <p>SERAGOLD HIGH PERFORMANCE TILE ADHESIVE MORTAR</p> <p>Cement based Tile tile adhesive with improved additional features. EN 12004 C2 T Class</p>	White	25 Kg. Craft Bag	64-80 Bag	5 KG/M2	
CE-104	 <p>SERATUT GRANITE TILE ADHESIVE MORTAR</p> <p>High performance, single component, cement based granite adhesive mortar improved with additional features. It is used for coating material like granite Tile tiles, natural granite, large sized Tile tiles, and porcelain Tile tiles. EN 12004 C2 T Class</p>	Gray	25 Kg. Craft Bag	64-80 Bag	5 - 6 KG/M2	
CE-105		White	25 Kg. Craft Bag	64-80 Bag		
CE-106		White	25 Kg. Craft Bag	64-80 Bag		



CE-108		<p>SERATUT KALIN YATAKLI SERAMİK YAPIŞTIRICI</p> <p>*Kayma özelliği azaltılmış ve açık bekletme süresi uzatılmış çimento esaslı özellikle bozuk zeminler için kalın yataklı seramik yapıştırma MORTARI.</p> <p>*Seramik vb. ağır plakalar mermer, traverten, granit, doğal taş vb. kaplama malzemelerinin kalın yataklı uygulama gerektiren durumlarda 2 cm. kalınlığa kadar iç ve dış mekanlarda duvara ve zeminlere uygulanır.</p> <p>EN 12004 C1 TE Class</p>	Gray	25 Kg. Craft Bag	64-80 Bag	7,5 - 10 KG/M2	
CE-109		<p>SERATUT TILE ADHESIVE MORTAR OVER TILE</p> <p>Tile adhesive mortar containing polymer additive with water repellent high adherence, reduced waiting time on the extended shift feature over elastic Tile. It is used directly onto old Tile surfaces with zero water absorption rate, such as new Tile plates used in interior and exterior of the walls and floors.</p> <p>EN 12004 C2 TE Class</p>	Gray	25 Kg. Craft Bag	64-80 Bag	5 - 6 KG/M2	
CE-110		<p>SERATUT TWO COMPENENT ELASTIC WATER PROOF TILE ADHESIVE MORTAR</p> <p>Cement based enhanced with special additives, two component of the high elasticity and the contribution of liquid adhesive mortar. Adhesive mortar bonding of Tile granite plate that provides waterproofing both interior and exterior laying medium and large sizes of plates to a height of 20 meters</p>	<p>A Compe nent Gray Powder</p> <p>B Compe nent White Liquid</p>	25 Kg. Craft Bag	6,25 Kg. Plastic Drum	As A Set 5 KG/M2	
CE-111		<p>SERAFLEX TILE ADHESIVE MORTAR</p> <p>Cement based, water-repellent, polymer additive, flexible adhesive mortar enhanced with additional features on the extended waiting period. It is used in coating Tile, porcelain tile, marble, granite, in wet areas such as bathroom and kitchen for indoor, outdoor floor and wall applications.</p> <p>EN 12004 C2 T Class</p>	Gray	25 Kg. Craft Bag	64-80 Bag	5 KG/M2	
CE-112		<p>SERAFLEX TILE ADHESIVE MORTAR</p> <p>Cement based, water-repellent, polymer additive, flexible adhesive mortar enhanced with additional features on the extended waiting period. It is used in coating Tile, porcelain tile, marble, granite, in wet areas such as bathroom and kitchen for indoor, outdoor floor and wall applications.</p> <p>EN 12004 C2 T Class</p>	White	25 Kg. Craft Bag	64-80 Bag	5 KG/M2	

CE-113		SERATUT AERATED CONCRETE ADHESIVE MORTAR  Cement based, Aerated Concrete adhesive mortar with high performance and polymer additives. It is used for installation of the structural elements like Aerated Concrete and brick with high water absorption capacity. EN 12004 C1 TE Class	Gray	25 Kg. Craft Bag	64-80 Bag	4 KG/M2	
CE-114		SERATUT FAST CURING TILE ADHESIVE MORTAR  Cement based, fast-curing adhesive mortar enhanced with additional features. It is used in coating materials such as Tile, marbles etc. for furnishing of wall and floor applications both interior and exterior. It can be grouted 4 hours after the application and enables easy combing after 6 hours and heavy combing after 12 hours. EN 12004 C2 F Class	Gray	25 Kg. Craft Bag	64-80 Bag	5 KG/M2	
CE-116		SERATUT NATURAL STONE AND DECORATIVE COATING BRICK ADHESIVE MORTAR  Cement based, high performance, polymer additive, water repellent adhesive mortar. It is used for bonding coating materials like natural stone and decorative coating bricks. EN 12004 C1 TE Class	Gray	25 Kg. Craft Bag	64-80 Bag	6 KG/M2	

LIQUID TILE ADHESIVE MORTAR







CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTION	PACK TYPE
AE-117		White	5 Kg. Plastic Bucket	As A Set	3 - 4 KG/M2	
AE-118	Ready to use, multi-purpose, acrylic emulsion based Tile adhesive mortar with high performance, water proofing. It is used in areas for bonding tiles on gypsum board, gypsum plaster and painted surfaces and Tile re-coating on old Tiles, mosaics and marble, surfaces like concrete, plaster and screed. EN 12004 D2 T Class	White	10 Kg. Plastic Bucket			

TWO COMPONENT EPOXY BASED GRANITE ADHESIVE

CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTION	PACK TYPE
EP-119	 <p>SERATUT EPOCOL TWO COMPONENT EPOXY BASED TILE ADHESIVE</p> <p>Epoxy based, two component, water impermeable to chemicals such as acid and alkali Tile adhesive and grout filler with high adherence and strength. It is used as Tile adhesive and grout filler interior and exterior spaces requiring resistance to acid and alkalis such as swimming pool, hospitals, and chemical industry. It is used in small and large sizes of Tiles that require resistance to acid and alkalis special interior and exterior spaces are as Tile adhesive.</p>	White	25 Kg. Craft Bag 6,25 Kg. Plastic Drum	A+B 12 Kg. Pl. Bucket	5,5 KG/M2	

GROUTING MATERIALS







CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTION	PACK TYPE
DD-120	 <p>SERADERZ COLORED GROUTING MATERIAL 0-6 MM</p> <p>Cement-based grouting material with polymer additives and water repellent features. It is used for coating tile, tiles, natural stones, granite tile and marbles, and 1-6 mm grout joints of the coating materials like floor and wall tiles, marble and natural stone.</p> <p>EN 13888 CD 2 Class</p>	White	20 Kg. Craft Bag	64-80 Bag	3MM FOR 0,7 KG/M2	
DD-121		LIGHT COLOUR TONES	20 Kg. Craft Bag	64-80 Bag	4 MM FOR 0,95 KG/M2	
DD-122		DARK COLOUR TONES	20 Kg. Craft Bag	64-80 Bag	6 MM FOR 1,5 KG/M2	
DD-123	 <p>SERADERZ FLEX COLORED GROUTING MATERIAL 0-6 MM</p> <p>Cement based colored grouting material with polymer additives, water repellent features and high adherence. It is used in applications of the coating materials such as tile, marble, granite in wet and very wet areas up to 1-6 mm.</p> <p>EN 13888 CD 2 Class</p>	White	20 Kg. Craft Bag	64-80 Bag	3MM FOR 0,7 KG/M2	
DD-124		LIGHT COLOUR TONES	20 Kg. Craft Bag	64-80 Bag	4 MM FOR 0,95 KG/M2	
DD-125		DARK COLOUR TONES	20 Kg. Craft Bag	64-80 Bag	6 MM FOR 1,5 KG/M2	

DD-126	 <p>SERADERZ COLORED GROUTING MATERIAL FOR LARGE SIZE GROUTS 3-20 MM</p> <p>Cement-based, elastic, colored grouting mortar with water-repellent features and polymer additives. It is used in places with intensive pedestrian and cargo traffic and wet areas. It is used as coating material for 6-20 mm grout joints of the coating materials especially like tile, granite tile, marble, granite, travertine, etc.</p> <p>EN 13888 CD 2 Class</p>		White	20 Kg. Craft Bag	64-80 Bag	6MM FOR 1,5 KG/M2				
DD-127			LIGHT COLOUR TONES					20 Kg. Craft Bag	64-80 Bag	8 MM FOR 2 KG/M2
DD-128			DARK COLOUR TONES					20 Kg. Craft Bag	64-80 Bag	20 MM FOR 3 KG/M2
DD-129	 <p>SERADERZ FLEX FLUID HIGH ABRASION-RESISTANT WATER-REPELLENT GROUTING MATERIAL</p> <p>Cement-based, high adherence, fluid structure, water-repellent and highly abrasion-resistant, gray mortar grouting. It is used in places with intensive pedestrian and cargo traffic, and wet areas. It is used as coating material for 1-6 mm grout joints of the coating materials like granite tile tiles, natural stone and marble.</p> <p>EN 13888 CD 2 Class</p>		Gray	20 Kg. Craft Bag	64-80 Bag	6MM FOR 1,5 KG/M2 8 MM FOR 2 KG/M2				

EPOXY GROUTING MATERIAL



CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTION	PACK TYPE
EPD-130	 <p>SERAtut Fugapox 1-15mm Epoxy Based Grouting Material</p> <p>*Epoksi esaslı, iki bileşenli, kimyasallara (özellikle asit ve alkalilere) karşı dayanıklı derz dolgu.</p> <p>Epoxy based, two component, chemical-resistant (acid and alkali) grouting material. It is used in places requires resistance against acid and alkalis, renewal for the worn-out grouts.</p>	White	A+B 3 Kg. Tin Box	As A Set	3MM FOR 0,9 KG/M2	
EPD-131		Gray	A+B 3 Kg. Tin Box	As A Set	5 MM FOR 1,5 KG/M2	
EPD-132		Black	A+B 3 Kg. Tin Box	As A Set	8 MM FOR 3 KG/M2	









LEVELLING REPAIR AND REINFORCEMENT SYSTEMS



CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTION	PACK TYPE
TH-133	 <p>SERAtut Concrete Surface Fine Repair Mortar TSEK</p> <p>Cement based, polymer additive, fiber-reinforced, high adherent, concrete repair mortar. It is used in all buildings for leveling and repairing of worn, broken and above ground drilled, It is used locally for leveling operations and the repairing of worn or broken concrete surfaces.</p>	Gray	25 Kg. Craft Bag	64-80 Bag	1MM THICKNESS 1,5 KG/M2	
TH-134	 <p>SERAtut Concrete Surface Course Repair Mortar TSEK</p> <p>Cement based polymer supported, fiber-reinforced surface repair mortar. It is used in all buildings for leveling and repairing of worn, broken and above ground drilled; it is used locally for leveling operations and the repairing of worn or broken concrete surfaces.</p>	Gray	25 Kg. Craft Bag	64-80 Bag	1MM THICKNESS 1,8 KG/M2	
TH-135	 <p>SERAtut WP-H High Strength Water Repellent Repairing Mortar TSEK</p> <p>Cement based, high-fiber-reinforced, polymer additive, waterproof, high adherence thyrrotrophic repairing mortar for concrete surfaces. It is used in repairing and leveling of all the buildings underground, above ground, under water grounds, all kinds of concrete, prefabricated concrete elements surface and the repairing of fractures in the corner, cross the cold joints, bevel material bridge viaducts, airplane hangars, landing-from runways, cold storage and so on. Overhead surfaces, ceiling and wall repair applications, the reinforcement bars as a result of erosion repair of damaged concrete, leveling and repairing mortar used as a molding. EN 13888 CD 2 Class</p>	Gray	25 Kg. Craft Bag	64-80 Bag	1MM THICKNESS 2 KG/M2	

GR-136		<p>SERAtut-240 High-Strength Fiber-Reinforced Non-Shrink Grout Mortar</p> <p>Special cement-based, high-strength fluid, fiber, special aggregate grouting mortar. It is resistant against freezing, thawing, and fuel and oil for concrete floor surfaces, high-strength forming, and hard surface. It is used in indoors and outdoors, large parking areas, parking decks, large shopping malls, large warehouse floors, all concrete floors exposed to heavy traffic, aircraft hangars and other areas over time wear, pitting, soil damage caused by breaking.</p>	Gray	25 Kg. Craft Bag	64-80 Bag	2 KG/LT	
GR-137		<p>SERAtut-60 Saatlik Dayanım Veren Rötresiz Kaplama ve Ankraj Grout MORTARI</p> <p>*Erken yüksek mukavemetli saatlik dayanım veren özel çimento esaslı akıcı dökülebilir yapıda grout MORTARI.</p> <p>*Rögar kapaklarının yükseltilmesinde, trafik levhalarının dikilmesi, beton ankrajlamalar (gömerek sabitleme) çatlak, boşluk ve oyukların doldurulması vb. uygulamalarda kullanılır.</p>	Gray	25 Kg. Craft Bag	64-80 Bag	2 KG/LT	







EPOXY BASED REPAIR AND FIXING MORTARS





CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTION	PACK TYPE
EPT-138	 <p>SERAtut Eporep-42 Two Component Epoxy Based Solvent Free Adhesive Mounting Mortar</p> <p>Two component, epoxy based with quartz combination grout. It is used to repair and stabilize the concrete surfaces for moderate thyrrotrophic and used as epoxy resin- based repairing and fixing mortar for concrete in bonding concrete to concrete, repairing of damaged areas fixing steel, concrete materials to concrete surfaces, bonding the broken edges of stairs etc.</p>	LIGHT Gray	A+B 5 Kg. Tin Box	As A Set	CONSUMPTION VARIABLE	

<p>EPT-139</p>		<p>SERAtut Eporep Thixo Two Component Thyrotrophic Based Solvent Free Bonding and Mounting Mortar</p> <p>Two component, epoxy based thyrotrophic bonding and mounting concrete mortar. It is used as fine coating adhesive for structural links and repairing operations. It is used in common building materials such as concrete, plaster, metal, tile, polyester, the assembly of prefabricated concrete elements of the columns, repairing of cracks and fractures, fixing iron sprouts in vertical and horizontal as surface protecting coating. It is chemical, abrasion and impact resistant with high mechanical strength.</p>	<p>LIGHT Gray</p>	<p>A+B 5 Kg. Tin Box</p>	<p>As A Set</p>	<p>CONSUMPTION VARIABLE</p>	
<p>EPT-140</p>		<p>SERAtut Cretpox Two-Component Epoxy Based Concrete Bonding Material</p> <p>Solvent free, epoxy based, two component, special additive and reinforcement protective bonding primer. It creates a bond between old and new concrete. It is used as a bonding material which protects iron equipment from corrosion, provides excellent adhesion between the old and new concrete and waterproofing, eliminates cold grout.</p>	<p>White</p>	<p>A+B 5 Kg. Tin Box</p>	<p>As A Set</p>	<p>1MM THICKNESS 1,2 KG/M2</p>	
<p>EPT-141</p>		<p>SERAtut Jelpox 05mm Transparent Solvent free Epoxy Injection Resin</p> <p>*Epoksi esaslı, iki bileşenli enjeksiyon reçinesi. Epoxy based, two component resin injection. It is used for bonding the cracks and cavities by filling max up to 5 mm wide and used to repair cracks in bridges, tunnels, industrial structures, columns, beams, foundations, walls and floors.</p>	<p>Transparent</p>	<p>A+B 3 Kg. Tin Box</p>	<p>As A Set</p>	<p>CONSUMPTION VARIABLE</p>	
<p>EPT-142</p>		<p>SERAtut Antipox Two Component Solvent Free Epoxy Based Reinforcement And Rust Inhibitor</p> <p>*Epoksi esaslı, iki bileşenli pas önleyici. Epoxy based, two component, rust inhibitor. It is used as anti-rust of the iron fittings.</p>	<p>LIGHT BLUE</p>	<p>A+B 3 Kg. Tin Box</p>	<p>As A Set</p>	<p>CONSUMPTION VARIABLE</p>	



<p>EPT-143</p>		<p>SERAtut Gropox-30 Three Component Cast Epoxy Resin Mortar (Grout)</p> <p>It is a solvent-free, 3-component, pourable grout, based on a combination of high strength epoxy resins and specially graded aggregates. After mixing, it provides a free flowing self-leveling epoxy grout. It can be applied on concrete, stone, mortar, steel, aluminum, asbestos, cement, wood, polyester and epoxy as a self-leveling, flowable epoxy mortar.</p>	<p>Sand Gray</p>	<p>A+B+C 3 Kg. Tin Box</p>	<p>As A Set</p>	<p>MIN. 12MM THICKNESS 18 KG/M2</p> <p>MAX. 50MM THICKNESS KG/M2</p>	
-----------------------	--	--	-------------------------	-----------------------------------	------------------------	--	---


CEMENT BASED PLASTERS





CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTION	PACK TYPE
<p>CS-144</p> <p>CS-145</p>	 <p>SERAtut Cement Based Machine Plaster</p> <p>Cement based fiber reinforced , high strength, plaster .It can be applied with machine to interior or exterior locations as to bricks, gas concrete, briquette walls, pumice concrete.</p>	<p>Gray</p> <p>White</p>	<p>35 Kg. Craft Bag</p> <p>35 Kg. Craft Bag</p>	<p>57 Bag</p> <p>57 Bag</p>	<p>1CM THICKNESS 17 KG/M2</p>	
<p>CS-146</p> <p>CS-147</p>	 <p>SERAtut Thick Hand Plaster</p> <p>Cement based, fiber reinforced thick plaster and applied with hand. It is used interior and exterior walls as thick hand plaster, applied to bricks, gas concrete, concrete, gross concrete, briquette walls and roof surfaces.</p>	<p>Gray</p> <p>White</p>	<p>35 Kg. Craft Bag</p> <p>35 Kg. Craft Bag</p>	<p>57 Bag</p> <p>57 Bag</p>	<p>1 CM THICKNESS 17 KG/M2</p>	
<p>CS-148</p> <p>CS-149</p>	 <p>SERAtut Fine Hand Plaster</p> <p>Cement based, fiber reinforced, ready to use super fine hand plaster and it is water repellent and high strength. It is used as a fine hand plaster for interior and exterior facades of all buildings.</p>	<p>Gray</p> <p>White</p>	<p>35 Kg. Craft Bag</p> <p>35 Kg. Craft Bag</p>	<p>57 Bag</p> <p>57 Bag</p>	<p>1MM THICKNESS 1,5 KG/M2</p>	

CS-150		SERAtut Super Fine Hand Plaster	Gray	35 Kg. Craft Bag	57 Bag	1MM THICKNESS 1,2 KG/M2	
CS-151		Cement based, fiber reinforced, ready to use super fine hand plaster and it is water repellent and high strength. It is used as latest plaster, which is ready to paint, interior and exterior walls, walls or roofs, and gross concrete.					
CS-152		SERAtut Concrete Surface Plaster	Gray	35 Kg. Craft Bag	57 Bag	1MM THICKNESS 1,7 KG/M2	
CS-153		Cement based, polymer supported, fiber reinforced hand plaster for concrete surfaces. It is applied to concrete surfaces, tunnels of all buildings as smooth plaster with hand.					
CS-154		SERAtut Plaster Satin Finishing Putty	Gray	20 Kg. Craft Bag	64-80 Bag	1MM THICKNESS 1 KG/M2	
CS-155		Cement based, polymer supported satin finishing putty. It is used in rendering plaster surfaces for interior and exterior of walls, repairing pits, holes, capillary cracks on surfaces.					



CEMENT BASED WATER INSULATION SYSTEMS









CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTION	PACK TYPE
WPC-156	 <p>SERAtut Cement based, Single Component, Crystalline, Capillary Efficient Water Insulation Material</p> <p>Single component, waterproofing slurry consisting of special additive and cement, penetrating into the concrete with capillary effect. It is used in external waterproofing of foundations basements lift shafts ,underground parking structures and storage rooms, water reservoirs, tunnels and galleries, structures below the groundwater level and subject to water penetration.</p>	Gray	25 Kg. Craft Bag	64-80 Bag	2MM THICKNESS 3 KG/M2	





<p>WPC-157</p>		<p>SERAtut Cem Quick Cement Based, Fast-Curing Water Sealing Mortar (Gray)</p> <p>Cement-based, capable of making very rapid setting water plugging mortar. It is used to stop and dry water leak on all kinds of surfaces, and in basements, lift shafts, underground parking structures and storage rooms, water reservoirs, and tunnels.</p>	<p>Gray</p>	<p>5 Kg. Plastic Bucket</p>		<p>1LT FOR 2 KG</p>	
<p>WPC-158</p>		<p>SERAtut Plaster Protection Plaster Against To Water, Humidity, Moisture</p> <p>Cement based, water repellent protection plaster which gives smooth surface against to moisture, humidity. It is used as insulation hand plaster interior and exterior, repairing old plaster exposed to water, moisture, humidity, surfaces of brick, concrete, pumice, gas concrete in a layer up to 2 cm.</p>	<p>Gray</p>	<p>25 Kg. Craft Bag</p>	<p>64-80 Bag</p>	<p>MİN. 1CM THICKNESS 17 KG/M2</p>	
<p>WPC-159</p>		<p>SERAsset-UV Single Component , UV Resistant, Water Insulation Material</p> <p>Single component, ready to use, uv resistant available for light pedestrian traffic insulation material which has elastic properties. It is not affected by temperature differences. Used as water insulation material in open-topped terraces, roofs, and pools which are wet volumes.</p>	<p>White Liquid</p>	<p>10 Kg. Plastic Drum</p>	<p>As A Set</p>	<p>MİN. 2MM THICKNESS 2 KAT 3 KG/M2</p>	
<p>WPC-160</p>		<p>SERAsset E-206 Two Component Full Elastic Waterproof Material</p> <p>*Cimento esaslı, polimer modifiyeli tam elastik fırça ile uygulanabilen su geçirimsizlik malzemesi. Cement based, polymer modified, waterproof material with full elastic applied with a brush. Cement and acrylic based water insulation material which can be applied with a brush over concrete requires waterproofing and high adherence, cement-based plaster. It is used for water tanks, foundations and basement walls, terraces, parapets and balconies, retaining walls etc.</p>	<p>A Component Gray Powder</p> <p>B Component White Liquid</p>	<p>20 Kg. Craft Bag</p> <p>10 Kg. Plastic Drum</p>	<p>As A Set</p>	<p>2 MM THICKNESS 2 KAT 3,5-4 KG/M2</p>	

<p>WPC-161</p>		<p>SERAsEt E-207 Two Component Elastic Water Insulation Material</p> <p>Cement based polymer modified elastic material applied with a brush. Cement and acrylic based water insulation material which can be applied with a brush over concrete requires waterproofing and high adherence, cement-based plaster. It is used for water tanks, foundations and basement walls, terraces, parapets and balconies, retaining walls etc.</p>	<p>A Component Gray Powder</p> <p>B Component White Liquid</p>	<p>20 Kg. Craft Bag</p> <p>10 Kg. Plastic Drum</p>	<p>As A Set</p>	<p>2MM THICKNESS 2 KAT 3,5-4 KG/M2</p>	
<p>WPC-162</p>		<p>SERAlastik Super Elastic Water Insulation Material</p> <p>Cement based polymer modified super elastic water insulation material applied with brush. It is used on concrete which requires high adherence, waterproofing, cement based plaster, insulation of underground basements, high-flow swimming pool, water tanks waste water and irrigation channels, recycling ponds. It is acid resistant material.</p>	<p>A Component Gray Powder</p> <p>B Component White Liquid</p>	<p>8 Kg. Plastic Bucket</p> <p>18 Kg. Plastic Bucket</p>	<p>As A Set</p>	<p>2 MM THICKNESS 2 KAT 2,5-3 KG/M2</p>	





LIQUID WATER ISOLATION SYSTEMS





CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTION	PACK TYPE
<p>WPL-163</p>	 <p>SERAsEt Elastiflex Adherence Increasing Water Impermeable Concrete And Mortar Additive</p> <p>Water impermeability liquid additive that fills the capillary pores and gives</p>	<p>White</p>	<p>3 Kg. Plastic Bucket</p>		<p>100KG CEMENT MORTAR WATER 1LT</p>	
<p>WPL-164</p>	<p>elasticity by reacting with cement and sand in the mixture of concrete and mortar. It is used as cement and mortar additive for the applications such as coating and plastering mortars, floor screeds, tunnels, foundations, culverts, water channels, water storage tanks and swimming pools, etc.</p>	<p>White</p>	<p>10 Kg. Plastic Bucket</p>			

<p>WPL-165</p>		<p>SERAtut Ultralastik Super Elastic Crack-Bridged Water Isolation Material</p> <p>Super elastic, single component, ready to use water isolation material that can be applied by brush or roll. It is used as super elastic water isolation material especially in flat and sloped roofs with large surface, channels and trunk, the edge of chimneys, eaves and gutters. It doesn't form any additional lot and suits to all types of surface. It can be diluted with water and it's always elastic, resistant to sunlight, easily applicable by brush or roll.</p>	<p>White</p>	<p>20 Kg. Plastic Bucket</p>		<p>1MM THICKNESS 1-1,5 KG/M2</p>	
<p>WPL-166</p>		<p>SERAtut Elastiroof Elastomeric Resin-Based Cream Consistent Water Isolation Material</p> <p>Single component, acrylic resin and elastic water based isolation material that can be applied by brush or roll. It can be used to provide water isolation in the surfaces such as tile, tile, spray polyurethane foam, zinc, aluminum, wood, brick, and bituminous veneers on terrace and roofs, screed concrete, and coated surfaces. It fills in the cracks up to 1-5mm and creates bridging cracks around the chimneys, vertical surfaces and water gutters.</p>	<p>White</p>	<p>20 Kg. Plastic Bucket</p>		<p>1 MM THICKNESS 2-2,5 KG/M2</p>	
<p>WPL-167</p>		<p>SERAtut Penetresil Silicon Based Penetrable Water Isolation Material</p> <p>Silicon supported, ready to use water isolation material that can easily penetrate on surfaces. It can be applied easily by everyone onto all cement based surfaces and fills in capillary space on the surface by penetrating.</p>	<p>Transparent</p>	<p>20 Kg. Tin Box</p>		<p>2 KATTA 0,150-0,200 KG/M2</p>	
<p>WPL-168</p>		<p>SERAtut Masticol Space-Grouting Elastic Water Isolation Material</p> <p>Single component, multi purpose, ready to use, paintable and elastic by taking air-cure space grouting material. It is used as water isolation grouting mastic to fill the immobile or less mobile joints and grouts or spaces around the edges of door and window, fixed equipment, fittings, kitchen countertops and bathtubs.</p>	<p>White</p>	<p>1 Kg. Plastic Bucket</p>		<p>CONSUMPTION VARIABLE</p>	





<p>WPL-169</p>		<p>SERAtut Elastidol Elastic and Fluid Water Proofing Dilatation Grouting Material</p> <p>High-adherent, water proofing grouting material which is used for every kind of elastic and fluid crack and dilatation spaces. It is used as crack filler for single component, ready to use, dilatation grouting and remains elastic after application.</p>	<p>White</p>	<p>20 Kg. Plastic Bucket</p>		<p>CONSUMPTION VARIABLE</p>	
<p>WPL-170</p>		<p>SERAtut Durapox Solvent Free Epoxy Based Water Isolation Material</p> <p>Solvent free, epoxy based, two-component hygienic water isolation material for reinforced concrete water storage tanks. It is used as water isolation material for metal and iron water storage tanks which are resistant to detergents, cleaners and chlorinated water and preventing the formation of bacteria and moss. It is highly resistant to chemicals and water for internal coating of drinking water storage tanks, easily cleaned thanks to its smooth and flat surface.</p>	<p>White</p>	<p>A+B 5 Kg. Tin Box</p>	<p>As A Set</p>	<p>2 LAYERS 0,3 MICRON FOR 0,150 KG/M2</p>	



CEMENT BASED HEAT INSULATION SYSTEMS

CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTION	PACK TYPE
<p>M-171</p>	 <p>SERAtut Plaster-Y Heat Insulation Board Coating Adhesive</p> <p>TSEK</p> <p>It is a cement based XPS and EPS heat insulation board coating adhesive. It is used in all constructions as heat insulation and rock wool slab coating adhesive.</p>	<p>Gray</p>	<p>25 Kg. Craft Bag</p>	<p>64-80 Bag</p>	<p>5,5 KG/M2</p>	
<p>M-172</p>	 <p>SERAtut Plaster-S Heat Insulation Board Coating Plastering Mortar</p> <p>TSEK</p> <p>It is cement based surface plaster for XPS and EPS heat insulation boards. In all constructions, it is applied as a top-coat plaster on the XPS, EPS and rock wool heat insulation boards.</p>	<p>Gray</p>	<p>25 Kg. Craft Bag</p>	<p>64-80 Bag</p>	<p>5,5 KG/M2</p>	





M-173	 <p>SERAtut Texture Cement Based Mineral Filled Decorative Plaster TSEK</p> <p>Cement-based, water repellent plaster. It is used as a decorative texture coating plaster for external top-coating which can be applied up to 2cm and gives decorative textured surface.</p>	White	25 Kg. Craft Bag	64-80 Bag	2MM THICKNESS 2-2,5 KG/M2	
M-174	 <p>SERAtut Styro Kleber XPS-EPS Liquid Adhesive</p> <p>It is an acrylic based liquid which is ready to be used for heat insulation systems. It is a high-additive and elastic, water proofing adhesive which can be used to paste XPS-EPS, rock wool and heat insulation plates onto the surfaces such as wood, gypsum board, sheet metal, metal interior and exterior.</p>	White	20 Kg. Plastic Bucket		3,5 KG/M2	

FLOOR PROTECTION AND COATING MATERIALS





CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTION	PACK TYPE
Z-175	 <p>SERAtut Hardfloor Quartz Aggregate Floor Hardener</p> <p>Mineral-based, quartz aggregate and self-colored surface hardener for concrete floors, which includes cement, pigments and chemical additives. It is used in the surfaces such as warehouses, wharves, heavy traffic roads, factory floors, shipyards, pedestrian paths, sidewalks, shop floors, parking lots, stations and garages. It is applied as monolithic to the new concrete for more aesthetic outlook and strengthens the floor coverings and screeds that require abrasion resistance.</p>	Gray	25 Kg. Craft Bag	64-80 Bag	4 KG/M2	
Z-176		Kırmızı	25 Kg. Craft Bag	64-80 Bag		
Z-177		Yeşil	25 Kg. Craft Bag	64-80 Bag		
Z-178	 <p>SERAtut 5-30 MM- Floor Screed</p> <p>Early high-strength granulometric structured special cement additive floor screed.</p>	Gray	25 Kg. Craft Bag	64-80 Bag	1CM THICKNESS 20 KG/M2	

Z-179		<p>SERAtut Self-Leveling Floor Laying Screed</p> <p>Cement-based, polymer modified, single component and ready to be used self-leveling floor laying screed. It is used as a floor laying screed for the floors that have been exposed to medium and high density pedestrian traffic to make them smooth before the last overlaying, to provide the desired smoothness of the ground on the floor in industrial floors, garages, workshops and warehouses and residential. It can be applied onto the old or new concrete surfaces.</p>	Gray	25 Kg. Craft Bag	64-80 Bag	1 MM THICKNESS 1,7 KG/M2	
-------	--	---	------	------------------	-----------	-----------------------------	---



MOLD RELEASE AGENTS







CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTION	PACK TYPE
Z-180	 <p>SERAtut Kapol-M Ready To Use Mineral Oil-Based Steel Mold Release</p> <p>Oil-based, mold release liquid used in less or non absorbency molds. It is used to separate steel, plastic, ply-wood molds easily from the concrete, to increase the efficiency of mold.</p>	Transparent	20 Kg. Plastic Drum		0,25 KG/M2	
Z-181	 <p>SERAtut Kapolin %12 Oil Based, Emulsion Of The Wood And Plywood With Water Steel Mold Release</p> <p>It is a high quality mineral oil with a mixture of private emulsifier. Oil concentrate separates molds easily which has water emulsion. It is used in all types of reinforced concrete mol, absorbent mold surfaces to separate wood molds easily from concrete, easy cleaning of molds, achieve a smooth concrete surface</p>	White	20 Kg. Plastic Drum		0,5 KG/M2	



CONCRETE CURING MATERIALS

CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTION	PACK TYPE
Z-182	 <p>SERAtut Serakür-HC Hydrocarbon Resin Based Curing Material</p> <p>Solvent based, single component, liquid curing material used for preventing rapid water loss, the risk of cracking due to rapid evaporation of mixing water and enabling optimum hardness of concrete. It is used in concrete floor coverings, surface hardener applied floorings, screed concrete, hot air conditioning of concrete castings, water tanks surfaces etc.</p>	Transparent	25 Kg. Plastic Drum		0,1 KG/M2	
Z-183	 <p>SERAtut Serakür-AC Acrylic Resin Based Concrete Curing Material</p> <p>A curing material for new concretes, mortars and surface hardeners. An acrylic resin based, single component curing material used for preventing the water loss in concrete, plaster, cement-based mortars and surface hardeners, the risk of cracking due to rapid evaporation of mixing water. It is used in concrete slabs, surface hardener applied floorings, parking lots and storage houses as a varnish for rough surfaces.</p>	White	25 Kg. Plastic Drum		0,15 KG/M2	



MORTAR ADDITIVES

CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTION	PACK TYPE
HK-184	 <p>SERAtut -1 Water Proof Liquid Mortar Additive</p> <p>Water proof mortar additive in the areas with normal setting plug. It ensures waterproofing by filling the gaps in the capillary concrete and mortar. It is used for coating, walling mortar and concrete such as tunnel, basement, culverts, canal and water reservoirs as liquid mortar additive.</p>	White	20 Kg. Plastic Drum		100 KG CEMENT FOR 1-3 LT	

<p>HK-185</p>		<p>SERAtut Latex Adherence Enhancing And Water Proofing Liquid Mortar Additive</p> <p>Liquid mortar additive enabling high adhesiveness and water proofing to mortar. It is used to increase the adherence, bending and tensile strength, elasticity and chemical resistance of mortars, and resistance of mortars against water abrasion. It enables binding for plaster, screed, concrete and construction joints and provides high adherence for the repair mortars, cement paint, foam and gas concrete surfaces.</p>	<p>White</p>	<p>25 Kg. Plastic Drum</p>		
<p>HK-186</p>		<p>SERAtut-G Liquid Volume Expanding Plastifiyen Mortar Powder Additive</p> <p>Plastifiyen powder mortar additive used in mortars instead of lime by adding micro-bubbles to the mixture, enabling liquid volume expanding and increasing fluidity. It enables easy process ability of cement by increasing the fluidity of cement and adhesion feature with excellent air-entraining.</p>	<p>White</p>	<p>20 Kg. Plastic Bucket</p>	<p>100 KG CEMENT FOR 0,1 KG MORTAR</p>	
<p>HK-187</p>		<p>SERAtut Retasol Plug Retarder Liquid Mortar Additive For Concrete And Mortars</p> <p>Plug retarder and normal plasticizer liquid mortar additive used in hot climate conditions. It is a liquid additive used in hot weather as plaster mortar for concreting, floor screeding. It is used for smooth concrete applications. It has prolonged setting time in hot weather, accelerates the hardening after setting, enables reducing the amount of water without decreasing operability and gives no harm to the iron equipment.</p>	<p>White</p>	<p>25 Kg. Plastic Drum</p>	<p>100 KG CEMENT FOR 2-3LT</p>	



HK-188		<p>SERAtut Antifreeze Liquid Mortar Additive Preserving the Concrete From Freezing in Cold Weather</p> <p>Reliable and chloride-free liquid mortar additive enabling rapid concreting by accelerating the plug in</p>	Transpa rent	7,5 Kg. Plastic Drum		100 KG CEMENT FOR 2-3LT	
HK-189		<p>low temperature. It is used to provide the continuity of work that requires cancellation of concreting due to the cold and frost risk. It is used for continuing light frost effect throughout the day, when frost is expected overnight and in cases of sudden temperature drop.</p> <p>Features/Advantages: Increases the resistance of mortars against freezing, sets and reduces the amount of time limitation necessary for the resistance against freezing.</p>	Transpa rent	20 Kg. Plastic Drum			

SURFACE PRIMERS

CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTIO N	PACK TYPE
AS-190	 <p>SERAtut Astarol Multi-Purpose Surface Primer</p> <p>Single component, multi purpose acrylic based copolymer primer by decreasing the absorbency of surfaces and increasing the bonding strength of cement based material. It is used as primer for gas concrete, limestone, brick, concrete walls and gypsum based coatings and adherence promoter primer reducing the absorption before the application of bonding screed, plaster and tiles under gypsum panel surfaces and applications of self-leveling floor screeds.</p>	White	20 Kg. Plastic Bucket		0,15 - 0,2 KG/M2	
AS-191	 <p>SERAtut Pürüzol Splicing Enhancer Surface Roughening Primer</p> <p>Quartz aggregate granulometric surface enhancing primer with high adhesion strength forming a rough surface on old glossy surfaces to provide the lining of large-scale of new tile. It is used as primer sticking to tile, wood, osb and metal surfaces providing the application of new coating on the old, bright, reduced absorption and friction free interior and exterior surfaces.</p>	White	20 Kg. Plastic Bucket		0,3 - 0,5 KG/M2	

STAIN REMOVERS AND PROTECTORS

CODE	PRODUCT NAME AND DESCRIPTION	COLOUR	PACK KG	TRAC K	CONSUMPTION	PACK TYPE
AS-192	 <p>SERAtut Fuga Guard Grout Protector and Stain Preventer</p> <p>Silicon-based, ready to use grout protector and stain preventer which penetrates into the grouts deeply. It is used to make the coating materials and grout joints resistant to dirt and corrosion. It protects kitchen and bathroom counters' joints against water and prevents stain formation, does not form a film layer on the surface and affect the natural outlook and colors of grouts.</p>	Transparent	500 Gr. Plastic Bucket		0,3 KG/M2	
AS-193	 <p>SERAtut Clean Ment Cement Stain Remover</p> <p>Cement stain remover reinforced with special chemicals. It is used to clean the top surfaces of tile, granite and natural stone coatings contaminated with cement based construction waste such as mortar and joint filler.</p>	Red	1 Kg. Plastic Bucket		0,5 - 0,7 KG/M2	
AS-194	 <p>SERAtut Stone Seal Natural Stone, Brick, Marble And Travertine Stain Preventer And Coating Material</p> <p>Protecting material that penetrates deeply into the coating materials such as natural stone, brick, marble and travertine. It is used as a protective material which is applied with anti dust and dirt waterproofing roll, brush or spray. It forms a thin layer on the surface.</p>	Transparent Shine	5 Kg. Tin Box		0,1 - 0,15 KG/M2	
AS-195	 <p>SERAtut Stone Seal Natural Stone, Brick, Marble And Travertine Stain Preventer And Coating Material</p> <p>Protecting material that penetrates deeply into the coating materials such as natural stone, brick, marble and travertine. It is used as a protective material which is applied with anti dust and dirt waterproofing roll, brush or spray. It forms a thin layer on the surface.</p>	Transparent Mate	5 Kg. Tin Box		0,1 - 0,15 KG/M2	

<p>AS-196</p>		<p>SERAtut Stone Seal Natural Stone, Brick, Marble And Travertine Stain Preventer And Coating Material</p> <p>Protecting material that penetrates deeply into the coating materials such as natural stone, brick, marble and travertine. It is used as a protective material which is applied with anti dust and dirt waterproofing roll, brush or spray. It doesn't form a layer on the surface.</p>	<p>Transpa rent</p>	<p>5 Kg. Tin Box</p>		<p>0,5 - 0,7 KG/M2</p>	
----------------------	--	---	--------------------------------	---------------------------------	--	-------------------------------	---