

Product Specifications Natural, ultra fine calcium carbonate manufactured from high purity and whiteness limestone.

Raw Material NiğDE

Chemical Properties	CaCO ₃	> 99,2 %
	MgCO ₃	< 0,30 %
	Fe ₂ O ₃	< 0,10 %
	SiO ₂	< 0,10 %
	Al ₂ O ₃	< 0,10 %
	HCl insoluble content	< 0,10 %

Physical Properties	Density (ISO 787-10)	2,7 gr/cm ³
	Hardness	3 Mohs
	Refractive Index	1,59

General Properties	Lightness , L* (ASTM E-313) Elrepho 450X _{min.}	98 %
	Brightness (Ry, DIN 53163) Elrepho 450X _{min.}	95 %
	Moisture-Ex.works (ISO 787-2) max.	0,3 %
	pH (ISO 787-9)	9
	Oil Absorption (ISO 787-5)	12 g/100 g
	Dop Absorption (ISO 787-5)	22 g /100 g
	Packed Bulk Densty (ISO 787-11)	1,3 g/ml

Main Applications Paper, paint, plastic, pvc granule, pvc profile and wick applications, cable, food, chemicals, rubber, insulation materials... etc.

Packaging 25 kg kraft paper bags, as bulk in big-bags.

Particle Size Distribution

d50 (mean particle size) max.	9 µm
d97 (top-cut) max.	68 µm
Under 2 µm particles(min.)	15 %
100 µm elek bakiyesi (ISO 787-7) max.	0,1 %

